



Yivli esnek kaplin Grooved flexible coupling

		Güncel boyutlar		Temel boyutlar			Basınç		Cıvatalar ve somunlar			Ağırlık
		Actual dimensions		Basic dimensions			Pressure		Bolts and nuts			Weight
Kırmızı Red	Galva	MM	DN	Ø MM	L MM	H MM	MPA	PSI	CIVATA BOYUTU BOLTSIZE MM	TORK TORQUE NM	LOKMA ANAHTARI SOCKET WRENCH	KG
GKFR 1	GKFG 1	33,7	25	55	97	45	2,5	300	M10*40	60-70	15	0,42
GKFR 1¼	GKFG 1¼	42,4	32	63,5	107,5	45	2,5	300	M10*50	60-70	15	0,48
GKFR 1½	GKFG 1½	48,3	40	69	114	45	2,5	300	M10*50	60-70	15	0,53
GKFR 2	GKFG 2	60,3	50	83,6	124	46	2,5	300	M10*60	60-70	15	0,71
GKFR 2½	GKFG 2½	76,1	65	98	139	46	2,5	300	M10*60	60-70	15	0,80
GKFR 3	GKFG 3	88,9	80	114	156	46	2,5	300	M10*60	60-70	15	0,97
GKFR 4	GKFG 4	114,3	100	142	189	50	2,5	300	M12*70	90-100	18	1,44
GKFR 5	GKFG 5	139,7	125	170	222	50	2,5	300	M12*70	90-100	18	1,89
GKFR 6	GKFG 6	168,3	150	198	251	50	2,5	300	M12*70	90-100	18	2,15
GKFR 8	GKFG 8	219,1	200	256	318	60	2,5	300	M16*85	200-230	24	3,77
GKFR 10	GKFG 10	273,0	250	319	393	64	2,5	300	M20*110	270-300	30	6,39