



U-Bolt sprinkler çıkışı, dişli BSPT U-bolt sprinkler outlet, threaded BSPT

		Güncel boyutlar		Temel boyutlar			Basınç		Cıvatalar ve somunlar			Delik kesimi		Ağırlık
		Actual dimensions		Basic dimensions			Pressure		Bolts and nuts			Hole cut		Weight
Kırmızı Red	Galva	MM	DN	L MM	H MM	A MM	MPA	PSI	CIVATA BOYUTU BOLTSIZE MM	TORK TORQUE NM	LOKMA ANAHTARI SOCKET WRENCH	MIN	MAX	KG
GSTR 1 - ½	GST 1 - ½	33,7x21,3	25-15	89	56	53	2,5	300	M8*44	25-30	13	25	26	0,33
GSTR 1¼ - ½	GST 1¼ - ½	42,4x21,3	32-15	89	56	53	2,5	300	M10*78	60-70	15	30	31	0,47
GSTR 1¼ - ¾	GST 1¼ - ¾	42,4x26,9	32-20	89	56	53	2,5	300	M10*78	60-70	15	30	31	0,46
GSTR 1¼ - 1	GST 1¼ - 1	42,4x33,7	32-25	89	56	56	2,5	300	M10*78	60-70	15	30	31	0,48
GSTR 1½ - ½	GST 1½ - ½	48,3x21,3	40-15	89	56	55	2,5	300	M10*78	60-70	15	30	31	0,39
GSTR 1½ - ¾	GST 1½ - ¾	48,3x26,9	40-20	89	56	55	2,5	300	M10*78	60-70	15	30	31	0,38
GSTR 1½ - 1	GST 1½ - 1	48,3x33,7	40-25	89	56	58	2,5	300	M10*78	60-70	15	30	31	0,41
GSTR 2 - ½	GST 2 - ½	60,3x21,3	50-15	98	56	64	2,5	300	M10*92	60-70	15	30	31	0,45
GSTR 2 - ¾	GST 2 - ¾	60,3x26,9	50-20	98	56	64	2,5	300	M10*92	60-70	15	30	31	0,45
GSTR 2 - 1	GST 2 - 1	60,3x33,7	50-25	98	56	67	2,5	300	M10*92	60-70	15	30	31	0,47